

REV.	DESCRIPTION	DATE	CHANGER
A/0	原始版本	19/07/17	

Current Rating: 1 Amps
 Insulator Resistance: 1000 Megohms min
 Dielectric Withstanding: 500 V AC
 Contact Resistance: 20m Min.
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: PA6T

Y B G 127 S0 X N -2 XX - C
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Box Header series
- ② Plastic Types
- ③ Pitch
- ④ Types-S: SMT
- ⑤ Plating-Gold Flash plated on nickel base
T: Tin plated on nickel base
D: Gold Flash/Tin plated on nickel base
G3: 3U" Gold
- ⑥ Plastic material- N: Nylon-6T
- ⑦ Row number-1: single 2: Double row
- ⑧ Number of Contacts-Unilateral quantity
- ⑨ CAP

Circuits	Dimension			Circuits	Dimension		
	A	B	C		A	B	C
6	2.54	18.31	8.46	34	20.32	36.09	26.24
10	5.08	20.85	11.00	40	24.13	39.90	30.05
12	6.35	22.12	12.27	44	26.67	42.44	32.59
14	7.62	23.39	13.54	50	30.48	46.25	36.40
16	8.89	24.66	14.81	60	36.83	52.60	42.75
20	11.43	27.20	17.35	64	39.37	55.14	45.29
26	15.24	31.01	21.16	66	40.64	56.41	46.56
30	17.78	33.55	23.70	68	41.91	57.68	47.83

YYE 东莞市源越电子有限公司
 DongGuan YuanYue Electronic CO., LTD.
 Web. : <http://www.yyecon.com>

公差: XX ±0.30 XXX ±0.20 XXXX ±0.10 X* ±3° X*X* ±2°	制圖: Jerry	日期: 2019.07.17	品名规格	
	审核:		1.27mm Box Header H:8.3 W:5.6 SMT (RoHS)	
 单位: mm 比例: 1:1 纸张: A4	核准:		料號: YBG127S0XN-2XX-C	
			图号:	B127S-0004

